

Bante 3 Series Portable pH/Ion Meter



Measurement Parameters

- Bante 320: pH, mV, relative mV, ion concentration, temperature
- Bante 321: Ion concentration, mV, temperature

Features

- pH
 - 1 to 5 points calibration with automatic recognition for USA, NIST and DIN buffers
 - Automatic electrode diagnosis shows the pH slope and zero offset
- ORP
 - 1 point offset calibration allows adjusting the displayed value to a known standard
 - Relative and absolute millivolt modes ensure the reliable ORP measurements
- Ion Concentration
 - 2 to 5 points calibration, including the selection of 8 concentration points
 - Automatic electrode diagnosis shows the calibration points and electrode slopes
 - Selectable concentration units (ppm, mg/L, mol/L) and ionic valency



General Features

- Automatic temperature compensation ensures accurate readings over the entire range
- Auto-read function senses and locks the measurement endpoint
- Calibration due alarm reminds users to calibrate the meter regularly
- Auto-power off effectively conserves battery life
- Setup menu allows setting the number of calibration points, resolution, stability criteria, temperature unit, date and time, etc.
- Reset function automatically restores all settings to the factory defaults
- Expanded memory stores or recalls up to 500 data sets
- USB communication interface enables easy data transfer to a PC
- Multi-mode power scheme (battery, power adapter and USB port) ensures the smooth operation of the meter

Optional Ion Selective Electrodes

Ammonium (NH_4^+), bromide (Br^-), cadmium (Cd^{2+}), calcium (Ca^{2+}), chloride (Cl^-), cupric (Cu^{2+}), cyanide (CN^-), fluoride (F^-), iodide (I^-), lead (Pb^{2+}), nitrate (NO_3^-), potassium (K^+), silver (Ag^+), sodium (Na^+), sulphide (S^{2-}), ammonia (NH_3)



Specifications

	Model	Bante 320	Bante 321
pH	Range	-2.000~20.000 pH	●
	Resolution	0.001, 0.01, 0.1 pH, selectable	●
	Accuracy	±0.002 pH	●
	Calibration	1 to 5 points	●
Ion	pH Buffer Options	USA, NIST, DIN, 2 custom buffers	●
	Range	0.001~19999 (depending on the range of ISE)	●
	Resolution	0.001, 0.01, 0.1, 1	●
	Accuracy	±0.5% F.S. (monovalent), ±1% F.S. (divalent)	●
	Measurement Units	ppm, mg/L, mol/L, mmol/L	●
ORP	Calibration	2 to 5 points	●
	Calibration Solutions	0.001, 0.01, 0.1, 1, 10, 100, 1000, 10000	●
	mV Range	±1999.9 mV	●
	Relative mV Range	±1999.9 mV	●
	Resolution	0.1, 1 mV, selectable	●
Temperature	Accuracy	±0.2 mV	●
	Calibration	1 point	●
	Range	0~105°C/32~221°F	●
	Resolution	0.1°C/0.1°F	●
	Accuracy	±0.5°C/±0.9°F	●
Other Specifications	Offset Calibration	1 point, reading ±10°C	●
	Temperature Compensation	0~100°C, manual or automatic	●
	Stability Criteria	Low or high	●
	Calibration Due Alarm	1 to 31 days or off	●
	Slope/Offset Display	Yes	●
	Hold Function	Manual or auto-endpoint	●
	Auto-Off	10, 20 or 30 minutes after last key pressed	●
	Memory	500 data sets	●
	Communication Interface	USB	●
	Connector	BNC, 3.5 mm jack socket	●
	Display	Custom LCD (80×60 mm)	●
	Power Requirements	3×1.5V AA batteries or 5V DC power adapter	●
	Battery Life	Approximately 150 hours (turn off the backlight)	●
	Dimensions	170(L)×85(W)×30(H) mm	●
	Weight	300g	●

Ordering Information

- Bante320-CN: Meter, E201-BNC plastic-body pH electrode, temperature probe, pH buffer solutions, electrode clip, carrying case
- Bante320-UK: Meter, P11 glass pH electrode, temperature probe, pH buffer solutions, electrode clip, carrying case
- Bante321: Meter, ion selective electrode, temperature probe, 100/1000 ppm standard solutions, ionic strength adjuster, electrode clip, carrying case