

# Bante 932 Benchtop Water Hardness Meter



## Features

- 2 to 5 points calibration from low to high concentrations
- Selectable water hardness units, including mmol/L, mg/L, german degree( $^{\circ}\text{dH}$ ), english degree( $^{\circ}\text{e}$ ) and french degree( $^{\circ}\text{f}$ )
- Automatic temperature compensation ensures accurate readings over the entire range
- Auto-read function senses and locks the measurement endpoint
- Calibration due alarm reminds users to calibrate the meter regularly
- Setup menu allows setting the number of calibration points, stability criteria, etc.
- Reset function automatically restores all settings to the factory defaults
- Expanded memory stores or recalls up to 500 data sets
- USB communication interface enables easy data transfer to a PC



## Ordering Information

Bante 932: Meter, ISE-WH water hardness electrode, temperature probe, 10/100 mmol/L standard solutions, ionic strength adjuster, electrode holder, USB cable, power adapter

## Specifications

	Model	Bante 932
Water Hardness	Range	0.05~200 mmol/L, 0~1122 $^{\circ}\text{dH}$ , 0~2000 $^{\circ}\text{fH}$ , 0~1404 $^{\circ}\text{e}$ , 0~8020 mg/L ( $\text{Ca}^{2+}$ ), 0~19999 mg/L ( $\text{CaCO}_3$ ), 0~11220 mg/L ( $\text{CaO}$ )
	Resolution	0.001, 0.01, 0.1, 1
	Accuracy	$\pm 1\%$ F.S.
	Calibration	2 to 5 points (0.01, 0.1, 1, 10, 100 mmol/L)
Temperature	Range	0.0~105.0 $^{\circ}\text{C}$
	Resolution	0.1 $^{\circ}\text{C}$
	Accuracy	$\pm 0.5\text{ }^{\circ}\text{C}$
	Offset Calibration	1 point, reading $\pm 10\text{ }^{\circ}\text{C}$
Other Specifications	Temperature Compensation	0~50 $^{\circ}\text{C}$ , manual or automatic
	Stability Criteria	Low or high
	Calibration Due Alarm	1 to 31 days or off
	Memory	500 data sets
	Communication Interface	USB
	Connector	BNC, 3.5 mm jack socket
	Display	Custom LCD (125×100 mm)
	Power Requirements	5V DC power adapter
	Dimensions	210(L)×188(W)×60(H) mm
	Weight	1.5 kg