

CON series Laboratory Conductivity Electrode

CON-1

Laboratory conductivity electrode, suitable for the general applications.



Measuring Range	10 μ S/cm~20mS/cm
Temperature Range	0~80°C, 32~176°F
Material	Platinum
Cell Constant	K=1
Body Type	Glass
Connector	6-pin mini plug, 1 meter cable
Dimensions	120(L) \times 12(Dia.)mm

CON-0.1

Laboratory conductivity electrode, suitable for measuring the pure water.



Measuring Range	0~100 μ S/cm
Temperature Range	0~80°C, 32~176°F
Material	Platinum
Cell Constant	K=0.1
Body Type	Glass
Connector	6-pin mini plug, 1 meter cable
Dimensions	120(L) \times 12(Dia.)mm

CON-10

Laboratory conductivity electrode, suitable for measuring the high conductivity liquids.



Measuring Range	100 μ S/cm~200mS/cm
Temperature Range	0~80°C, 32~176°F
Material	Platinum
Cell Constant	K=10
Body Type	Glass
Connector	6-pin mini plug, 1 meter cable
Dimensions	120(L) \times 12(Dia.)mm

IE-50 series Industrial Conductivity Electrode

FEATURES

- IE-50LT: suitable for measuring the low conductivity liquids.
- IE-50MT: suitable for the general applications.
- IE-50HT: suitable for measuring the high conductivity liquids.

Model	IE-50LT	IE-50MT	IE-50HT
Measuring Range	0~100 μ S/cm	0~20mS/cm	0~200mS/cm
Cell Constant	K=0.1	K=1	K=10
Material	Platinum		
Temperature Sensor	10K Ω		
Connector	3/4" male NPT, 5 meters cable		
Dimensions	150(L) \times 29.5(Dia.)mm		

